

2007-2016 JEEP JK WRANGLER JK WRANGLER GRILLE INSTALLATION STRUCTIONS 20"DUAL ROW LED LIGHT BAR

*Lights Sold Separately



KIT INCLUDES

- Grille
- Button Head Screws
- Top and Bottom Brackets Nuts
- Side Brackets
- Washers


IMPORTANT

Thank you for purchasing grill for your Jeep. Installation is fairly simple with the right tools and good mechanical abilities. If you are not confident in your mechanical skills, please seek the help of a professional to perform the installation. Please read through all of these instructions and tips before proceeding with the installation. It is strongly recommended that this product be installed by a professional.

Installation of this product requires cutting of your factory installed grille. Your factory grille will be unusable after it has been cut. This product has more surface area than your factory grille. It may reduce airflow into your vehicle. Reduction in airflow can potentially lead to overheating issues. This product has been pre-bent to fit the contour of your vehicle grille shell. However, it may have partially flattened during shipping. It may be necessary for you to reshape in order to get a good fit.

Always disconnect any power sources connected to your vehicle before servicing fuses or electrical systems.


KIT EXAMPLE



STEP 1

Remove(2)press-in buttons and save for re-use. See Figure 1.

Figure 1:(Only one side shown)



STEP 2

Remove(4)10mm bolts and save for re-use. See Figure 2.


Figure 2:



STEP 3

Pinch(4)clips at the bottom of the grille shell release grille. See Figure 3.

Figure 3:



STEP 4

Twist and turn fog lights out of grille shell remove grille shell. See Figure 4.

Figure 4:




STEP 5

Cut template out, align on grille, and secure to grille. See Figure 5.

Figure 5:




Figure 5.1:



STEP 6

With a pick tool, firmly mark(12)inside holes along edge. This will be your cut guide. See Figure 6.

Figure 6:



STEP 7

Drill(4)outer corner holes on template with 5/16 drill bit. See Figure 7.

Figure 7:



WARRANTY INFORMATION

Warranty Periods:

- .All LED Lights-1Year
- .Accessories and Mounts-1Year

All of the following will immediately void all warranties:

- .Customer negligence-The customer has modified the light and/or is not using it for the recommend application.
- .Customer abuse-Damage to light beyond normal wear and tear.
- .If the light has been opened or any screws have been removed.

STEP 8

Remove template, use tape as a straight edge following the previously marked (12) holes. See

Figure 8:



Figure 8.1:


**STEP 9**

Use an air saw, Dremel, or similar tool, to cut out grille using taped straight edge as a guideline. See Figure 9.

Figure 9:



Figure 9.1:


**STEP 10**

Place Bar grille on shell and install (4) 1/4-20x5/8 Long Button Head Screws, (4) 1/4-20 Nyloc Nuts, (4) 1/4-20 Washers in the corners of the grille. See Figure 10.

Figure 10:



Figure 10.1:

**STEP 11**

Install (2) top and bottom mounting brackets and (2) side mounting brackets with (12) 1/4-20x5/8 Long Button Head Screws, (12) 1/4-20 Nyloc Nuts, (12) 1/4-20 SS Washers. See Figure 11.

Figure 11:






Figure 11.1:

**STEP 12**


Install 20" Dual light using the hardware provided with the light. See Figure 12.

Figure 12:

**STEP 13**

Re-connect factory fog lights and press our grille into the vehicle snapping (4) factory clips into place. Re-insert (2) press-in buttons saved from step 1. See Figure 13.

Figure 13:

**STEP 14**

Re-install (4) 10mm screws saved from step 2. See Figure 14.

Figure 14:



Your installation is now

